

HEADSTONE SPECIFICATIONS

All memorial headstones shall be constructed from granite or other naturally occurring stone approved by Council.

CHILDREN'S LAWN

Height of base	100 mm
Length of base	915 mm
Width of base	200 mm

These headstones can be desks or plates and stand on marble, granite or concrete plastered bases. The thickness of the stones shall not exceed 100 mm. The width of the stones shall not exceed 450 mm. **The overall height of base and stone combined shall not exceed 500 mm.** The rear margins will be 50 mm.

CREMATION MEMORIAL LAWN – SECTION T

Height of base	100 mm
Length of base	610 mm
Width of base	200 mm

These headstones are to be desks only 100/55 on Marble or Granite bases. The thickness of the stones shall not exceed 100 mm. The breadth of the stones shall not exceed 450 mm. **The overall height of base and stone combined shall not exceed 500 mm.** The rear margin will be 50 mm.

CREMATION LAWN – U 2A

Height of base	100 mm
Length of base	610 mm
Width of base	200 mm

These headstones can be desks or plates and stand on Marble, Granite or Concrete plastered bases. The thickness of stones shall not exceed 100 mm. The breadth of stones shall not exceed 450 mm. **The overall height of base and stone combined shall not exceed 500 mm.** The rear margin will be 50 mm.

MEMORIAL PLAQUE AREAS

Garden Kerb Bronze Plaque	150 mm x 100 mm
U-1A Granite Plaque	360 mm x 230 mm x 16 mm
Sands Memorial Granite Plaque	200 mm x 150mm x 16 mm

LAWN CEMETERY FULL BURIAL PLOTS

Height of base	50 -150 mm
Length of base	single plot: up to 1220 mm
Length of base	double plot: no less than 1220 mm, up to 2440 mm
Width of base	330 mm

These headstones can be desks or plates and stand on marble, granite or concrete plastered bases. The thickness of the stones shall not exceed 150 mm, normally with a tolerance of 30 mm for rock-backed stones. **The overall height of the base and stone combined shall not exceed 1000 mm.** The rear margin will be 50 - 75 mm.

The breadth of stones for single plots shall not exceed 950 mm.
The breadth of stones for double plots shall not exceed 1220 mm.

All concrete bases to have a minimum of one 5 mm reinforcing rod running length ways.

All memorials shall be constructed and secured in accordance with the requirements of NZS4242:1995 Headstones and Cemetery Monuments and subsequent revisions.